



## RID Workforce Aerosol RID Australia

Chemwatch Hazard Alert Code: 4

Chemwatch: 59-9990  
Version No: 5.1.1.1  
Safety Data Sheet according to WHS and ADG requirements

Issue Date: 25/06/2020  
Print Date: 24/08/2020  
S.GHS.AUS.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

Product name	RID Workforce Aerosol
Synonyms	620150 Workforce Aerosol 150g
Proper shipping name	AEROSOLS
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Medicated insect bite treatment and personal insect repellent in aerosol form. Application is by spray atomisation from a hand held aerosol pack Use according to manufacturer's directions.
--------------------------	--

#### Details of the supplier of the safety data sheet

Registered company name	RID Australia
Address	30 Bernoulli Street Darra QLD 4076 Australia
Telephone	1300 041 772
Fax	1300 360 440
Website	<a href="http://www.rid.com.au">www.rid.com.au</a>
Email	Not Available

#### Emergency telephone number

Association / Organisation	RID Australia
Emergency telephone numbers	+61 7 47721411
Other emergency telephone numbers	Not Available

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code.

#### ChemWatch Hazard Ratings

	Min	Max	
Flammability	4		
Toxicity	1		0 = Minimum
Body Contact	2		1 = Low
Reactivity	1		2 = Moderate
Chronic	0		3 = High
			4 = Extreme

Poisons Schedule	Not Applicable
Classification [1]	Flammable Aerosols Category 1, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements

Hazard pictogram(s)	
---------------------	--

RID Workforce Aerosol

Signal word	Danger
-------------	--------

Hazard statement(s)

H222	Extremely flammable aerosol.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
AUH044	Risk of explosion if heated under confinement.

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.

Precautionary statement(s) Storage

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
-----------	--

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64-17-5	30-60	ethanol
134-62-3	19.1	N,N-diethyl-m-toluamide
Not Available	balance	Ingredients determined not to be hazardous
74-98-6	}26	propane
106-97-8.	}	butane

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul style="list-style-type: none"> <li>· Intended for application to skin.</li> <li>· Remove with soap and water if irritation occurs.</li> <li>· Seek medical advice if irritation persists.</li> </ul>
Inhalation	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

**Extinguishing media****SMALL FIRE:**

- ▶ Water spray, dry chemical or CO2

**LARGE FIRE:**

- ▶ Water spray or fog.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition with violent container rupture.</li> <li>▶ Aerosol cans may explode on exposure to naked flames.</li> <li>▶ Rupturing containers may rocket and scatter burning materials.</li> <li>▶ Hazards may not be restricted to pressure effects.</li> <li>▶ May emit acrid, poisonous or corrosive fumes.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) nitrogen oxides (NO<sub>x</sub>) other pyrolysis products typical of burning organic material.</p> <p><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p>
<b>HAZCHEM</b>	Not Applicable

**SECTION 6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Shut off all possible sources of ignition and increase ventilation.</li> <li>▶ Wipe up.</li> <li>▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.</li> <li>▶ Undamaged cans should be gathered and stowed safely.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</b></li> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse / absorb vapour.</li> <li>▶ Absorb or cover spill with sand, earth, inert materials or vermiculite.</li> <li>▶ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.</li> <li>▶ Undamaged cans should be gathered and stowed safely.</li> <li>▶ Collect residues and seal in labelled drums for disposal.</li> <li>▶ Remove leaking cylinders to a safe place if possible.</li> <li>▶ Release pressure under safe, controlled conditions by opening the valve.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 Handling and storage****Precautions for safe handling**

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> </ul>
----------------------	--

RID Workforce Aerosol

	<ul style="list-style-type: none"> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ <b>DO NOT spray directly on humans, exposed food or food utensils.</b></li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed. Contents under pressure.</li> <li>▶ Store away from incompatible materials.</li> <li>▶ Store in a cool, dry, well ventilated area.</li> <li>▶ Avoid storage at temperatures higher than 40 deg C.</li> <li>▶ Store in an upright position.</li> <li>▶ Protect containers against physical damage.</li> <li>▶ Check regularly for spills and leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<p>The Can manufacturer pressure tests these epon lined cans to 15-18 Bar as per Australian Standard AS 2278.1. [Mfr]</p> <ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>



+ — Must not be stored together  
 X — May be stored together with specific preventions  
 + — May be stored together

**SECTION 8 Exposure controls / personal protection**

**Control parameters**

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	butane	Butane	800 ppm / 1900 mg/m3	Not Available	Not Available	Not Available

**Emergency Limits**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethanol	Ethanol: (Ethyl alcohol)	Not Available	Not Available	15000* ppm
propane	Propane	Not Available	Not Available	Not Available
butane	Butane	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
ethanol	3,300 ppm	Not Available
N,N-diethyl-m-toluamide	Not Available	Not Available
propane	2,100 ppm	Not Available
butane	Not Available	1,600 ppm

**Occupational Exposure Banding**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
N,N-diethyl-m-toluamide	E	≤ 0.1 ppm

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

**Exposure controls**

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p>
---	--

## RID Workforce Aerosol

	<p>Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.</p> <p>Provide adequate ventilation in warehouse or closed storage areas.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <tr> <td>Type of Contaminant:</td> <td>Speed:</td> </tr> <tr> <td>aerosols, (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <tr> <td>Lower end of the range</td> <td>Upper end of the range</td> </tr> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Type of Contaminant:	Speed:	aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s	direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
Type of Contaminant:	Speed:																
aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s																
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)																
Lower end of the range	Upper end of the range																
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity																
3: Intermittent, low production.	3: High production, heavy use																
4: Large hood or large air mass in motion	4: Small hood-local control only																
Personal protection																	
Eye and face protection	<p>No special equipment for minor exposure i.e. when handling small quantities.</p> <p><b>OTHERWISE:</b> For potentially moderate or heavy exposures:</p> <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ <b>NOTE:</b> Contact lenses pose a special hazard; soft lenses may absorb irritants and <b>ALL</b> lenses concentrate them.</li> <li>▶ Close fitting gas tight goggles</li> </ul> <p><b>DO NOT wear contact lenses.</b></p> <ul style="list-style-type: none"> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>																
Skin protection	See Hand protection below																
Hands/feet protection	<p>Wear general protective gloves, eg. light weight rubber gloves.</p> <ul style="list-style-type: none"> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ <b>OTHERWISE:</b></li> <li>▶ For potentially moderate exposures:</li> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures:</li> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>																
Body protection	See Other protection below																
Other protection	<p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eyewash unit.</li> <li>▶ Do not spray on hot surfaces.</li> <li>▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.</li> <li>▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.</li> </ul> <p>BREThERICK: Handbook of Reactive Chemical Hazards.</p>																

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

RID Workforce Aerosol

Material	CPI
BUTYL	A
NEOPRENE	A
NITRILE	A

## Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2 P2	AX-PAPR-2 P2 ^
up to 10 x ES	-	AX-3 P2	-

Continued...

NITRILE+PVC	A
PE/EVAL/PE	A
PVC	B
NATURAL RUBBER	C
NATURAL+NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

10+ x ES	-	Air-line**	-
----------	---	------------	---

\* - Continuous Flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Pale yellow flammable liquid with a mild odour; partially miscible with water (50% of liquid is water soluble). Supplied as an aerosol pack. Contents under <b>PRESSURE</b> . Contains highly flammable hydrocarbon propellant.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.82
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	78 (initial)	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	<-81 (propellant)	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	70-80
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Partly miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
----------------	---

	<p>Inhalation of toxic gases may cause:</p> <ul style="list-style-type: none"> <li>▶ Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;</li> <li>▶ respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;</li> <li>▶ heart: collapse, irregular heartbeats and cardiac arrest;</li> <li>▶ gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.</li> </ul> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p><b>WARNING: intentional misuse by concentrating/inhaling contents may be lethal.</b></p>																																				
<b>Ingestion</b>	<p>Accidental ingestion of the material may be damaging to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments</p>																																				
<b>Skin Contact</b>	<p>The liquid may be able to be mixed with fats or oils and may decrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Application of Deet to the skin produces no primary skin irritation or sensitisation in humans. In rabbits, redness and peeling of the skin have been observed as well as intoxication, excitation, stiffness and loss of co-ordination. Harm to the foetus has been reported following application of large doses. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material</p>																																				
<b>Eye</b>	<p>This material can cause eye irritation and damage in some persons.</p>																																				
<b>Chronic</b>	<p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Based on experience with similar materials, there is a possibility that exposure to the material may reduce fertility in humans at levels which do not cause other toxic effects. Exposure to DEET is usually by inhaling mists or vapours, or through skin contact/absorption. Repeated exposure to DEET can cause slight irritation and dryness of the face, sloughing around the nose and a tingling sensation. Some individuals have shown nervous system symptoms (muscle cramp, urinary hesitation, difficulty sleeping, abnormal sweating, irritability, depression, paranoia, confusion and aggressive behaviour) and brain disease. Allergy and scarring skin inflammation have been reported; in one case, a 5-year-old girl died, likely as a result of sensitisation to DEET.</p> <p>Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.</p>																																				
<b>RID Workforce Aerosol</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available																																
TOXICITY	IRRITATION																																				
Not Available	Not Available																																				
<b>ethanol</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>1.40 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit): 500 mg SEVERE</td> </tr> <tr> <td>1400 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit):100mg/24hr-moderate</td> </tr> <tr> <td>4070 mg/kg<sup>[2]</sup></td> <td>Eye: adverse effect observed (irritating)<sup>[1]</sup></td> </tr> <tr> <td>4070 mg/kg<sup>[2]</sup></td> <td>Skin (rabbit):20 mg/24hr-moderate</td> </tr> <tr> <td>5100 mg/kg<sup>[2]</sup></td> <td>Skin (rabbit):400 mg (open)-mild</td> </tr> <tr> <td>6030 mg/kg<sup>[2]</sup></td> <td>Skin: no adverse effect observed (not irritating)<sup>[1]</sup></td> </tr> <tr> <td>6030 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>6080 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>6080 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>9200 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>9710 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Inhalation (rat) LC50: 0 mg/l/10h<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Inhalation (rat) LC50: 124.7 mg/l/4H<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Inhalation (rat) LC50: 63926.976 mg/l/4h<sup>[2]</sup></td> <td></td> </tr> <tr> <td>mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Oral (rat) LD50: =1501 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Oral (rat) LD50: 7060 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	1.40 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg SEVERE	1400 mg/kg <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate	4070 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	4070 mg/kg <sup>[2]</sup>	Skin (rabbit):20 mg/24hr-moderate	5100 mg/kg <sup>[2]</sup>	Skin (rabbit):400 mg (open)-mild	6030 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	6030 mg/kg <sup>[2]</sup>		6080 mg/kg <sup>[2]</sup>		6080 mg/kg <sup>[2]</sup>		9200 mg/kg <sup>[2]</sup>		9710 mg/kg <sup>[2]</sup>		Inhalation (rat) LC50: 0 mg/l/10h <sup>[2]</sup>		Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup>		Inhalation (rat) LC50: 63926.976 mg/l/4h <sup>[2]</sup>		mg/kg <sup>[2]</sup>		Oral (rat) LD50: =1501 mg/kg <sup>[2]</sup>		Oral (rat) LD50: 7060 mg/kg <sup>[2]</sup>	
TOXICITY	IRRITATION																																				
1.40 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg SEVERE																																				
1400 mg/kg <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate																																				
4070 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>																																				
4070 mg/kg <sup>[2]</sup>	Skin (rabbit):20 mg/24hr-moderate																																				
5100 mg/kg <sup>[2]</sup>	Skin (rabbit):400 mg (open)-mild																																				
6030 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>																																				
6030 mg/kg <sup>[2]</sup>																																					
6080 mg/kg <sup>[2]</sup>																																					
6080 mg/kg <sup>[2]</sup>																																					
9200 mg/kg <sup>[2]</sup>																																					
9710 mg/kg <sup>[2]</sup>																																					
Inhalation (rat) LC50: 0 mg/l/10h <sup>[2]</sup>																																					
Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup>																																					
Inhalation (rat) LC50: 63926.976 mg/l/4h <sup>[2]</sup>																																					
mg/kg <sup>[2]</sup>																																					
Oral (rat) LD50: =1501 mg/kg <sup>[2]</sup>																																					
Oral (rat) LD50: 7060 mg/kg <sup>[2]</sup>																																					
<b>N,N-diethyl-m-toluamide</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>35 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit) : 10 mg - moderate</td> </tr> <tr> <td>4750 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit): 100 mg</td> </tr> <tr> <td>950 mg/kg<sup>[2]</sup></td> <td>Skin (rabbit): 500 mg - moderate</td> </tr> <tr> <td>Dermal (rabbit) LD50: 3180 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>dermal (rat) LD50: 5000 mg/kg<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Inhalation (rat) LC50: 5.95 mg/l<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Oral (rat) LD50: 1800 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	35 mg/kg <sup>[2]</sup>	Eye (rabbit) : 10 mg - moderate	4750 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg	950 mg/kg <sup>[2]</sup>	Skin (rabbit): 500 mg - moderate	Dermal (rabbit) LD50: 3180 mg/kg <sup>[2]</sup>		dermal (rat) LD50: 5000 mg/kg <sup>[2]</sup>		Inhalation (rat) LC50: 5.95 mg/l <sup>[2]</sup>		Oral (rat) LD50: 1800 mg/kg <sup>[2]</sup>																					
TOXICITY	IRRITATION																																				
35 mg/kg <sup>[2]</sup>	Eye (rabbit) : 10 mg - moderate																																				
4750 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg																																				
950 mg/kg <sup>[2]</sup>	Skin (rabbit): 500 mg - moderate																																				
Dermal (rabbit) LD50: 3180 mg/kg <sup>[2]</sup>																																					
dermal (rat) LD50: 5000 mg/kg <sup>[2]</sup>																																					
Inhalation (rat) LC50: 5.95 mg/l <sup>[2]</sup>																																					
Oral (rat) LD50: 1800 mg/kg <sup>[2]</sup>																																					
<b>propane</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Inhalation (rat) LC50: &gt;49942.95 mg/l/15M<sup>[2]</sup></td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Inhalation (rat) LC50: >49942.95 mg/l/15M <sup>[2]</sup>	Not Available																																
TOXICITY	IRRITATION																																				
Inhalation (rat) LC50: >49942.95 mg/l/15M <sup>[2]</sup>	Not Available																																				

butane	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 658 mg/l/4H <sup>[2]</sup>	Not Available

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

N,N-DIETHYL-M-TOLUAMIDE	<p>For N,N-diethyl-m-toluamide (Deet)</p> <p><b>Acute toxicity:</b> Different preparations of Deet with different proportions of the m-isomer produced different oral LD50s. Rats killed by dosages in the LD50 range showed lacrimation, chromodacryorrhea, depression, prostration, tremors, and asphyxial convulsions. Respiratory failure usually preceded cardiac failure.</p> <p>In rabbits, an intravenous dosage of 75 mg/kg was rapidly fatal, but 50 mg/kg was not. Five doses at the rate of 25 mg/kg/day produced no cumulative effect, except for injury of the intima of some veins used for injection. Single dermal applications to rabbits at rates of 2 or 4 ml/kg produced no systemic effect, but did produce mild to moderate erythema. Repeated dermal application of 50% solutions for 13 weeks at the rate of 2 ml/kg/day produced no evidence of systemic toxicity but did produce desquamation, coriaceousness, dryness, and fissuring in the same species. Except for some scarring, these lesions cleared within 3 weeks. Instillation of Deet into the eyes of rabbits produced mild to moderate edema of the nictitating membrane, lacrimation, conjunctivitis, and some corneal injury, as revealed by fluorescein staining. After 5 days, all eyes appeared normal. No sensitisation was seen in guinea pigs .</p> <p>Animals topically exposed to Deet have developed dermal and ocular reactions. Dermal effects including erythema, desquamation and scarring in rabbits and profuse sweating, irritation and exfoliation in horses have been reported following repeated applications of Deet at concentrations of 50 percent or greater. Direct ocular application of either diluted (30 or 40 percent Deet) or undiluted Deet in rabbits has produced edema, tearing, conjunctivitis, pus and clouding in the eyes.</p> <p>Repeated dermal application to horses produced hypersteatosis, an overactivity of the sebaceous glands, when the solution of Deet was 15% or higher.</p> <p>Dermal application in humans of insect repellents containing Deet can produce a variety of skin reactions in humans. Cases of localized skin irritation, large painful blisters and permanent scarring of skin at the crease of the elbow have been reported in soldiers who applied solutions of 50 or 75 percent Deet. Results from questionnaire surveys conducted by the National Institute for Occupational Safety and Health (NIOSH) among Everglades National Park Employees indicated a variety of dermal reactions including rashes, irritation of skin and mucous membranes, and numb or burning sensations of the lips among park workers who were highly exposed to Deet-containing repellents. Urticaria or dermatitis, resulting from topical Deet exposure has been noted in both children and adults. In one instance involving only limited Deet exposure, the urticaria was accompanied by an anaphylactic reaction .</p> <p>Controlled human exposure studies using 50 or 75 percent Deet have reproduced many of the dermal effects noted in field studies. The U.S. Army conducted an investigation in volunteers using 75 percent Deet applied to the upper arm and elbow's crease. Of the 77 volunteers, 37 (48%) had severe dermal reactions at the crease of the elbow. No dermal reactions were observed on the upper arm or in the control group of men tested with ethanol solvent alone.</p> <p>Several cases of toxic encephalopathy associated with the use of Deet in children have been reported in the medical literature. The first reported case involved a 3.5 year old girl whose body, bedclothes and bedding were sprayed each night for two weeks with an insect repellent containing 15 percent Deet. Since then, five additional cases of toxic encephalopathy have been temporally associated with the use of Deet products in children, all of whom were females . The toxic encephalopathy was characterised by agitation, weakness, disorientation, ataxia, seizures, coma and in three cases resulted in death. Autopsies conducted on two fatalities indicated oedema of the brain, with one case presenting necrotic lesions in the cerebellum and spinal cord and an enlarged liver accompanied by microscopic changes. One child was reported to be heterozygous for ornithine carbamoyl transferase deficiency (a sex linked enzyme deficiency which may produce effects similar to those reported above) and it has been hypothesised that children with this enzyme disorder may be at greater risk of adverse reactions to Deet. This enzyme deficiency which usually causes infant death in males is of variable severity in females. Accidental and deliberate ingestion of Deet-containing products has produced neurotoxic effects similar to those described following dermal exposure .</p> <p>Generalised seizures have also been temporally associated with the use of Deet-containing insect repellent on skin . These cases differ from those described above in that they involved males (four boys aged 3-7 years and one 29-year-old adult), had few associated neurotoxic effects and resolved rapidly. Lower exposure to Deet in these males (four of five males had either one or two dermal applications) may have accounted for the effects being less severe than in females. That the majority of identified neurotoxic cases involved children raises concerns that this subpopulation is at greater risk of adverse reaction following exposure to Deet than are adults.</p> <p>Signs and symptoms of more subtle neurotoxicity have also been associated with extensive dermal application of Deet in adults. Questionnaire results indicate that Everglades National Park employees having extensive Deet exposure were more likely to have insomnia, mood disturbances and impaired cognitive function than were lesser exposed co-workers. A young male who repeatedly applied Deet to his skin prior to spending prolonged periods in a sauna was reported to develop acute manic psychosis characterized by aggressive behavior, delusions and hyperactivity. Either o-DET or p-DET, or both occur as impurities in commercial m-DET (Deet). A thorough study of the o-and p-isomers showed that the o-isomer is slightly more toxic than the others (oral LD50 1,210 mg/kg in rats). However, no alarming difference was found, and it was concluded that the presence of 5% of o-DET or p-DET as impurities in the</p> <p><b>Chronic toxicity:</b> When rats were fed Deet at a dietary level of 10,000 ppm for about 200 days, their growth rate was decreased without a decrease in food intake. There was a significant increase in the relative weight of the testes and liver in males, of the liver and spleen in females, and the kidneys of both males and females. Some of these changes were seen in lesser degree at a dietary level of 1,000 ppm. No gross or significant histological changes were seen at any dietary level and no changes of any kind were noted at 100 ppm or 500 ppm (about 25 mg/kg/day).</p> <p>Essentially identical results were found in other subacute dermal and feeding studies each carried out on rats, rabbits, and dogs. In these oral studies, 2,000 ppm proved to be a no-effect-level. Oral administration of Deet to dogs at rates of 100 and 300 mg/kg/day caused tremor and hyperactivity and occasional vomiting, but no other effects. Blood studies (hemoglobin, haematocrit, sedimentation rate, platelet counts, total and differential white cell counts) on dogs receiving 300 mg/kg orally or dermally or on rabbits receiving 300 mg/kg dermally revealed no effect on the haematopoietic system. Gross and microscopic examination of the organs of all three species revealed only slight kidney damage in rabbits typical of that associated with burns of the skin. Thirteen other organs, including liver, spleen, and bone marrow, were normal in the three species .</p> <p>No systemic toxicity was observed in rats exposed 8 hours/day, 5 days/week for 7 weeks to air saturated with Deet. No toxic effects were observed in rats exposed for 6 hours to an aerosol of Deet. No gross or significant histological changes were seen .</p> <p><b>Organ Toxicity:</b> Hypertrophy of the kidneys and liver and effects of mild central nervous system stimulation including tremors and hyperactivity were noted in animals following repeated exposure. Significant testicular hypertrophy was observed in male rats repeatedly fed a diet containing from 48 to 531 mg/kg/day of Deet</p> <p><b>Reproductive Effects:</b> When Deet was applied to the skin of rats at the rate of 1,000 mg/kg/day throughout pregnancy, implantation was reduced significantly. Prenatal mortality was 34.1%, compared with 20.9% in the control. Mortality between birth and weaning was 44.0%, compared to 15.7% in the control. Injury was less (but probably significant) at a dosage of 100 mg/kg/day throughout pregnancy.</p> <p><b>Teratogenic Effects:</b> A dermal teratology study was conducted on rabbits. Groups of 20 pregnant rabbits received daily dermal applications of 0, 50, 100, 500, 1000, or 5000 mg Deet/kg/day in ethanol on shaved backs from day 0 through day 29 of gestation. There were no significant differences between control and treated animals with respect to the fertility index, number of implantations per animal, or number of fetuses per animal. In addition, treatment did not change fetal weight, fetal length or placental weights and no increases in the incidence of skeletal or soft tissue anomalies were observed in treated groups when compared with untreated controls. This study demonstrated that Deet has no teratogenic or embryotoxic effects in rabbits exposed dermally to technical Deet.</p> <p>An additional supplementary teratology study was conducted on rats. Groups of 20 pregnant rats were daily administered 10 ml of peanut oil containing 0, 8, 20 or 80 mg/kg/Deet by gavage from day 5 through day 15 of gestation. No significant differences were reported between control and treated mothers with respect to fertility, fetuses per litter, foetal weight or foetal survival. However, the study did show decreases in number of implantation sites per dam and number of fetuses per animal. In addition, a related increase was observed in the number of resorptions per dam</p>
-------------------------	---



	<p><b>Carcinogenicity:</b> Researchers fed Deet to male and female rats in the diet for two years at doses of 10, 30, or 100 mg/kg/day, and 30, 100, or 400 mg/kg/day, respectively. Researchers fed mice 250, 500, or 1,000 mg/kg/day for 18 months, and dogs 30, 100, or 400 mg/kg/day. No specific target organ toxicity or oncogenicity was observed in any of the animals. Researchers often use studies designed to test for mutagenicity to screen chemicals for carcinogenicity. Sufficient evidence indicates that DEET does not have significant potential for mutagenicity</p> <p><b>Fate in Humans and Animals:</b> Deet is absorbed promptly from the skin and distributed to all organs including the brain and the foetus. The compound is excreted in the milk but primarily in the urine</p> <p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>Reproductive effector in rats</p>
<b>RID Workforce Aerosol &amp; PROPANE</b>	No significant acute toxicological data identified in literature search.
<b>RID Workforce Aerosol &amp; ETHANOL &amp; N,N-DIETHYL-M-TOLUAMIDE</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	✗
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

RID Workforce Aerosol	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
ethanol	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	11-mg/L	2
	EC50	48	Crustacea	>10-mg/L	2
	EC50	96	Algae or other aquatic plants	ca.22-mg/L	2
NOEC	168	Algae or other aquatic plants	1-296mg/L	2	
N,N-diethyl-m-toluamide	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
propane	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	24.11mg/L	2
	EC50	96	Algae or other aquatic plants	7.71mg/L	2
butane	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	24.11mg/L	2
	EC50	96	Algae or other aquatic plants	7.71mg/L	2
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

#### Environmental Fate:

Soil: N,N-diethyl-m-toluamide (DEET), an active ingredient in insect repellent, is found to be moderately mobile in soil and is stable to hydrolysis at soil pH level typically found in the environment. Studies show that DEET can be biodegraded by soil microorganism e.g. *P. putida*.

Water: DEET, practically insoluble in water, was detected in water as a result of urban wastewater contamination to stream-flow.

Air: DEET, exist as gas in the atmosphere, can be degraded by reaction with hydroxyl radicals.

#### Ecotoxicity:

Birds LD50: 1375 mg/l

Fish LC50 (96h): rainbow trout 172 ppm

Fish LC50: 75 mg/l

Aquatic invertebrates EC50: 75ppm

For Ethanol:

log Kow: -0.31 to -0.32;

Koc 1: Estimated BCF= 3;

Half-life (hr) air: 144;

Half-life (hr) H2O surface water: 144;

Henry's atm m3 /mol: 6.29E-06;

BOD 5 if unstated: 0.93-1.67,63%

COD: 1.99-2.11,97%;

ThOD : 2.1.

Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation. Ethanol is expected to have very high mobility in soil. Volatilization of ethanol from moist soil surfaces is expected to be an important fate process. The potential for volatilization of ethanol from dry soil surfaces may exist.

Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms.

**Atmospheric Fate:** Ethanol is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days. Ethanol readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

**Aquatic Fate:** When released into water ethanol readily evaporates and is biodegradable. Ethanol is not expected to adsorb to suspended solids and sediment. Volatilization from water surfaces is expected and volatilization half-lives for a model river and model lake are 3 and 39 days, respectively. Bioconcentration in aquatic organisms is considered to be low. Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol and is unlikely to be persistent in aquatic environments.

For Propane: Koc 460. log Kow 2.36.

Henry's Law constant of  $7.07 \times 10^{-1}$  atm-cu m/mole, derived from its vapour pressure, 7150 mm Hg, and water solubility, 62.4 mg/L. Estimated BCF: 13.1.

**Terrestrial Fate:** Propane is expected to have moderate mobility in soil. Volatilization from moist soil surfaces is expected to be an important fate process. Volatilization from dry soil surfaces is based vapor pressure. Biodegradation may be an important fate process in soil and sediment.

**Aquatic Fate:** Propane is expected to adsorb to suspended solids and sediment. Volatilization from water surfaces is expected and half-lives for a model river and model lake are estimated to be 41 minutes and 2.6 days, respectively. Biodegradation may not be an important fate process in water.

**Ecotoxicity:** The potential for bioconcentration in aquatic organisms is low.

**Atmospheric Fate:** Propane is expected to exist solely as a gas in the ambient atmosphere. Gas-phase propane is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 14 days and is not expected to be susceptible to direct photolysis by sunlight.

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
N,N-diethyl-m-toluamide	HIGH	HIGH
propane	LOW	LOW
butane	LOW	LOW

### Bioaccumulative potential

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
N,N-diethyl-m-toluamide	LOW (BCF = 2.4)
propane	LOW (LogKOW = 2.36)
butane	LOW (LogKOW = 2.89)

### Mobility in soil

Ingredient	Mobility
ethanol	HIGH (KOC = 1)
N,N-diethyl-m-toluamide	LOW (KOC = 536.6)
propane	LOW (KOC = 23.74)
butane	LOW (KOC = 43.79)


## SECTION 13 Disposal considerations

### Waste treatment methods

<b>Product / Packaging disposal</b>	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ Bury residues and emptied aerosol cans at an approved site.</li> </ul>
-------------------------------------	---

## SECTION 14 Transport information

### Labels Required

	
<b>Marine Pollutant</b>	NO

<b>HAZCHEM</b>	Not Applicable
----------------	----------------

**Land transport (ADG)**

<b>UN number</b>	1950	
<b>UN proper shipping name</b>	AEROSOLS	
<b>Transport hazard class(es)</b>	Class	2.1
	Subrisk	Not Applicable
<b>Packing group</b>	Not Applicable	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	63 190 277 327 344 381
	Limited quantity	1000ml

**Air transport (ICAO-IATA / DGR)**

<b>UN number</b>	1950	
<b>UN proper shipping name</b>	Aerosols, flammable	
<b>Transport hazard class(es)</b>	ICAO/IATA Class	2.1
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	10L
<b>Packing group</b>	Not Applicable	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	A145 A167 A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1950	
<b>UN proper shipping name</b>	AEROSOLS	
<b>Transport hazard class(es)</b>	IMDG Class	2.1
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	Not Applicable	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	EMS Number	F-D , S-U
	Special provisions	63 190 277 327 344 381 959
	Limited Quantities	1000 ml

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture****ethanol is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

**N,N-diethyl-m-toluamide is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

**propane is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

**butane is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -  
Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)  
Chemical Footprint Project - Chemicals of High Concern List

### National Inventory Status

National Inventory	Status
Australia - AIIC	Yes
Australia Non-Industrial Use	No (ethanol; N,N-diethyl-m-toluamide; propane; butane)
Canada - DSL	Yes
Canada - NDSL	No (ethanol; N,N-diethyl-m-toluamide; propane; butane)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### SECTION 16 Other information

<b>Revision Date</b>	25/06/2020
<b>Initial Date</b>	23/09/2015

### SDS Version Summary

Version	Issue Date	Sections Updated
4.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
5.1.1.1	25/06/2020	Synonyms, Name

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average  
PC – STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.